

# Masking

# Tape



## **5995 Malaysia**

- About Us
- Sticky Story
- Global Distribution
- Our Standards

## **Masking Tape**

- Utility
- Professional
- Performance
- Precision
- Extreme



With more than 40 years of experience in the Adhesive Tape market, **OBS Packaging** is popularly known for its sticky solutions.

We currently distribute and supply our premium performance solutions to diverse industries, working closely with our distributors worldwide.

Committed to providing premium products at the best value to our global consumers, we are

**#yourpartnerinadhesivetape**

1978 | Trading Enterprise  
1988 | 2x Converting Facilities  
1995 | Overseas Venture – **OBS Packaging**  
2006 | Distribution Across Asia Pacific  
2008 | ISO 9001 and ISO 14001 Certified  
2012 | Coating / Blowing Partner  
2016 | Distribution Across Europe & America  
2018 | 12x Converting Facilities  
2019 | Overseas Venture – 5995 Malaysia  
2020 | Preferred Partner of 180+ Private Labels

***Sticky Story***

## ***Europe:***

- 📍 Germany
- 📍 United Kingdom
- 📍 France
- 📍 Italy
- 📍 Spain
- 📍 Greece
- 📍 Poland
- 📍 Ireland
- 📍 Hungary
- 📍 Denmark
- 📍 Sweden
- 📍 Belgium

## ***Middle East:***

- 📍 Turkey
- 📍 Israel
- 📍 United Arab Emirates
- 📍 Qatar
- 📍 Kuwait

## ***America:***

- 📍 United States
- 📍 Canada
- 📍 Mexico
- 📍 Argentina

## ***Asia:***

- 📍 Singapore
- 📍 Malaysia
- 📍 Thailand
- 📍 The Philippines
- 📍 Laos
- 📍 Myanmar
- 📍 Cambodia
- 📍 Indonesia
- 📍 China
- 📍 Taiwan
- 📍 Sri Lanka
- 📍 South Korea
- 📍 Hong Kong
- 📍 Vietnam
- 📍 India

***Global Distribution***

**Certificate Of Assessment  
International Quality Certification**

hereby grants to:

**OBS Packaging (M) Sdn Bhd**

whose quality management system is in conformance with the standard:

**ELOT EN ISO 9001:2008**

the right to be listed in the IQC Registry for the following scope(s):

**PRODUCTION OF GLUE - PRODUCTION AND SALES OF SELF ADHESIVE  
TAPES AND OTHER PACKAGING MATERIALS**

Signed



CEO

on behalf of IQC

This Certificate Number **GR/149/2003-1**  
REISSUED ON **4/12/2015**  
IS VALID UNTIL **3/12/2018**



Doiranis 191 Str., GR-17673 Kallithea, Hellas

**Certificate Of Assessment  
International Quality Certification**

hereby grants to:

**OBS Packaging (M) Sdn Bhd**

whose quality management system is in conformance with the standard:

**ELOT EN ISO 14001:2004**

the right to be listed in the IQC Registry for the following scope(s):

**PRODUCTION OF GLUE - PRODUCTION AND SALES OF SELF ADHESIVE  
TAPES AND OTHER PACKAGING MATERIALS**

Signed



CEO

on behalf of IQC

This Certificate Number **GR/149/2003-3**  
REISSUED ON **4/12/2015**  
IS VALID UNTIL **3/12/2018**










Doiranis 191 Str., GR-17673 Kallithea, Hellas

**Our Standards**

The image features a collection of adhesive tapes arranged horizontally. From left to right, there are several rolls of tape in different colors: brown, yellow, and tan. In the foreground, a roll of white tape is partially unrolled, revealing a red patterned interior with the word "Kram" repeated. The word "Utility" is superimposed in a large, bold, black script font across the center of the image.








*Utility*

Model No. (#5980)	Material & Colour	Adhesive	Total Thickness (mic)	Adhesion to Steel (N/in)	Elongation (%)	Temperature Resistance (°C)	Water Resistant	UV Resistant
80A	Crepe Paper 	Natural Rubber	120	> 4	8	60	-	-
55Y	Crepe Paper 	Natural Rubber	130	> 6	10	60	-	-
90A	Crepe Paper 	Natural Rubber	125	> 4.5	9	60	-	-
25P	Crepe Paper 	Natural Rubber	130	> 6.3	8	60	-	-
35A	Crepe Paper 	Natural Rubber	130	> 3.5	10	90	-	-
36Y	Crepe Paper 	Natural Rubber	160	> 6	14	60	-	-
19V	Crepe Paper 	Natural Rubber	125	> 5.5	9	60	Yes	-





***Professional***

Model No. (#5995)	Material & Colour	Adhesive	Total Thickness (mic)	Adhesion to Steel (N/in)	Elongation (%)	Temperature Resistance (°C)	Water Resistant	UV Resistant
90A	Crepe Paper 	Natural Rubber	120	> 4.5	9	60	-	-
63A	Crepe Paper 	Natural Rubber	130	> 7.5	9	80	-	-
88A	Crepe Paper 	Natural Rubber	135	> 9.5	9	80	-	-
15P	Crepe Paper 	Natural Rubber	125	> 5.0	8	90	Yes	-
50A	Crepe Paper 	Natural Rubber	130	> 3.2	10	100	Yes	-
84U	Crepe Paper 	Natural Rubber	140	> 7.25	10	80	Yes	-
40A	Crepe Paper 	Natural Rubber	140	> 5.5	10	80	Yes	-

















**Technical Information and Product Use**

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, ISO, government agencies or Omark Worldwide, Quality Assurance and Technical Service departments. Figures shown refer to average values only, based on tests carried out in laboratory with controlled environmental conditions and are not valid for specification. The company reserves the right to modify or change the products at any time without notice.

The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. Omark Worldwide reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. Customers are required to do their own testing under their working condition for their intended application.

A collection of colorful adhesive tape rolls is arranged on a white background. The rolls are in various colors: yellow, orange, green, and blue. Some rolls are standing upright, while others are lying flat in the foreground. The word "Performance" is written in a large, bold, black serif font across the center of the image, partially obscuring the tapes. The inner labels of the tapes are visible, showing the brand name "Krämo" in red text on a white background.

**Performance**

Model No. (#5993)	Material & Colour	Adhesive	Total Thickness (mic)	Adhesion to Steel (N/in)	Elongation (%)	Temperature Resistance (°C)	Water Resistant	UV Resistant
64S	Crepe Paper 	Natural Rubber	135	> 6.0	8	85	Yes	-
40A	Crepe Paper  	Natural Rubber	140	> 5.5	10	80	Yes	-
30V	Crepe Paper  	Natural Rubber	135	> 7.2	9	100	Yes	Yes (7 Day)
34A	Crepe Paper 	Natural Rubber	130	> 3.2	10	100	Yes	-
41A	Crepe Paper  	Natural Rubber	140	> 5.5	11	120	Yes	-
36P	Crepe Paper    	Natural Rubber	135	> 6.9	8	90	Yes	-
99A	Crepe Paper    	Natural Rubber	145	> 4.5	8	120	Yes	-

**Technical Information and Product Use**










Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, ISO, government agencies or Omark Worldwide, Quality Assurance and Technical Service departments. Figures shown refer to average values only, based on tests carried out in laboratory with controlled environmental conditions and are not valid for specification. The company reserves the right to modify or change the products at any time without notice.

The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. Omark Worldwide reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. Customers are required to do their own testing under their working condition for their intended application.





***Precision***

Model No. (#5965)	Material & Colour	Adhesive	Total Thickness (mic)	Adhesion to Steel (N/in)	Elongation (%)	Temperature Resistance (°C)	Water Resistant	UV Resistant
50O	Washi Paper 	Acrylic, Water Based	100	> 4.0	8	120	Yes	Yes (1 Day)
30P	Washi Paper 	Acrylic, Water Based	90	> 3.6	3.5	80	Yes	Yes (20 Day)
35V	Washi Paper  	Acrylic, Water Based	85	> 5.0	3	120	Yes	Yes (3 Day)
40P	Washi Paper 	Acrylic, Water Based	90	> 4.2	3.5	120	Yes	Yes (3 Day)
36R	Washi Paper 	Acrylic, Water Based	80	> 2.5	5	120	Yes	-
31A	PVC Film  	Natural Rubber	120	> 1.6	150	150	Yes	-
37A	PVC Film 	Natural Rubber	120	> 1.5	180	150	Yes	-

**Technical Information and Product Use**

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, ISO, government agencies or Omark Worldwide, Quality Assurance and Technical Service departments. Figures shown refer to average values only, based on tests carried out in laboratory with controlled environmental conditions and are not valid for specification. The company reserves the right to modify or change the products at any time without notice.

The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. Omark Worldwide reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. Customers are required to do their own testing under their working condition for their intended application.



**Extreme**

<b>Model No. (#5993)</b>	<b>Material &amp; Colour</b>	<b>Adhesive</b>	<b>Total Thickness (mic)</b>	<b>Adhesion to Steel (N/in)</b>	<b>Elongation (%)</b>	<b>Temperature Resistance (°C)</b>	<b>Water Resistant</b>	<b>UV Resistant</b>
50V	Crepe Paper	Natural Rubber	150	> 7.9	9	120	Yes	Yes (10 Day)
90S	Crepe Paper	Acrylic, Solvent Based	130	> 4.75	8.5	-	Yes	Yes (15 Day)
21P	Crepe Paper	Acrylic, Water Based	135	> 3.5	9	-	Yes	Yes (7 Day)
85S	Crepe Paper	Acrylic, Water Based	130	> 3.75	8.5	-	Yes	Yes (7 Day)
51V	Crepe Paper	Acrylic, Water Based	145	> 6.2	9	120	Yes	Yes (10 Day)
93A	Crepe Paper	Acrylic, Water Based	135	> 3.0	10	-	Yes	Yes (7 Day)
12S	Crepe Paper	Natural Rubber	145	> 8.3	10	-	Yes	Yes (7 Day)

#### Technical Information and Product Use

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, ISO, government agencies or Omark Worldwide, Quality Assurance and Technical Service departments. Figures shown refer to average values only, based on tests carried out in laboratory with controlled environmental conditions and are not valid for specification. The company reserves the right to modify or change the products at any time without notice.

The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. Omark Worldwide reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. Customers are required to do their own testing under their working condition for their intended application.



OBS Packaging (M) Sdn Bhd

**Newways**

(60) 6543 9712 / 9714

stickysolution@obspackaging.com

www.obspackaging.com